

EOS NOCUT VV910



CUT RESISTANCE SUPPORT WITH HIGH PERFORMANCE POLYETHYLENE GLOVE - NITRILE-COATING PALM **Ref.** VV910







Product specifications

Cut resistance support with high performance polyethylene. Neoprene reinforcement on back and fingertips. Smooth nitrile coating/foam nitrile on palm and fingertips. Embossed inside reinforcement on palm. Kevlar® thread on all the seams.

COLOUR

Yellow-Grey-Black

SIZE

08, 09, 10, 11

Product Use - Risks





Cutting / Perforation Wearing







Services / Logistics



Construction / Civil engineering

Heavy industry





Product's highlights & user's benefits



Reinforcement between the thumb and index finger and on the palm

Double nitrile coating to work in oil environments:

- First smooth nitrile coating: Oil permeability
- Second foam nitrile coating: Good grip



Protection of the metacarpals 5 J



Flexible reinforcements for better protection against impact and pinching.

Very good resistance to abrasion and cutting

Wash in cold water

8 cm cuff: safety and comfort

Kevlar® thread for a longer durability of the glove



Available only with header card

Protection against impact in metacarpal area. For an energy impact of 5 J, the maximum force transmitted to the back of the hand must be less than 4 kN.



Certifications and Standards



PPE DIRECTIVE 89/686/EEC

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)



EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 4: Resistance to abrasion (from 1 to 4)
- 5: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)

EN1621-1 Clothing for protection against mechanical shock

References					
References	Bar code	COLOUR	SIZE	•	À
VV910JA08	3295249191542	Yellow-Grey-Black	08	60	12
VV910JA09	3295249191559	Yellow-Grey-Black	09	60	12
VV910JA10	3295249191566	Yellow-Grey-Black	10	60	12
VV910JA11	3295249191573	Yellow-Grey-Black	11	60	12